



MARKING SERVICES, INC.

BRASS VALVE TAGS



DESCRIPTION

Use brass valve tags to tag valves, instruments, small piping, cables or fugitive emission locations. Solid brass "S" hooks, #16 brass jack chain, #6 solid brass bead chain, nylon ties, lead meter seals or zinc snap hooks are available to attach valve tags. Each is a tough, sturdy, and corrosion resistant fastener.

*Stamped and black-filled

*Packaged in sets of 25 consecutive numbers

*Custom sizes, shapes and gauges available by special order

PHYSICAL PROPERTIES

Standard Material: Brass

Standard Thickness: 20 gauge (0.032" thick (0.812 mm))

Optional Thickness: Available on request

Standard Colors: BRASS (BLACK text)

Non-standard Colors: Additional text colors available on request

Mounting: Ø3/16" (Ø4,8mm) default diameter

Finish: Matte finish

Text Height: 1/4" service indicator on the top line & 1/2" #'s on bottom line

Available Characters: 1/8" Text , # / \ " - . ' ° () A thru Z - all upper case & 0 thru 9

1/4" Text , # / \ " - . ' ° A thru Z - all upper case & 0 thru 9

Typical sizes (H x W): 1.5" (38 mm) diameter 1.5" x 1.5" (38 mm x 38 mm)

2" (51 mm) diameter 2" x 2" (51 mm x 51 mm)

1 x 3" (25 mm x 76 mm) Other (specify: height x width)

The Maximum # of characters per line

Tag Size

Max # 1/4" char

Max No Lines

1.5" rnd & sq w/ 3 - 1/2 #'s

5

1

2" rnd & sq w/ 3 - 1/2 #'s

1st line 5, 2nd 6

2

1.5" rd - characters only

1st line 4, 2nd 5, 3rd 4

3

1.5" sq - characters only

5

3

2" rd & sq- characters only

1st line 6, 2nd 7, 3rd 6

3

Tag Size

Max # 1/8" char

Max No Lines

1.5" rnd & sq w/ 3 - 1/2 #'s

8

2

2" rnd & sq w/ 3 - 1/2 #'s

8

3

1.5" rd & sq- characters only

8

3

2" rd & sq - characters only

10

3