



MS-264 ENGRAVED PLASTIC CABLE TAGS

Technical Data



Description

MS-264 engraved plastic equipment tags are ideal for marking electrical cables in control panels. Engraved information clearly shows against background. Tags are notched for secure installation using standard 50 lb. cable ties. Standard tag construction is 2-ply, 1/16" thick.

Although MS-264 is not a thermoset plastic (phenolic) as designated by ASTM-D709 it is a fire-retardant polymer specifically designed as a safer, formaldehyde and phenol free, alternative to phenolic. MS-264 is non-flammable, UL 94 VO rated, electrically non-conductive, and insulative. Tags are also RoHS compliant, halogen free and PVC free.

Physical and Chemical Characteristics

Standard Material:	2-ply (two laminated layers of engraving plastic)	
Standard Thickness:	1/16" (1.6 mm)	
Service Temperature:	-20°F through 175°F (-29°C through 79°C)	
Finish:	Matte finish with beveled edges	
Mounting:	Notches fit standard 50 lb. cable ties	
Text Height:	Sized to fit within tag boundary or comply with specified height	
Standard Colors: (Non-standard colors available upon request)	<input type="checkbox"/> BLACK (WHITE text) <input type="checkbox"/> GREEN (WHITE text) <input type="checkbox"/> RED (WHITE text) <input type="checkbox"/> BLUE (WHITE text)	<input type="checkbox"/> WHITE (BLACK text) <input type="checkbox"/> YELLOW (BLACK text) <input type="checkbox"/> ORANGE (BLACK text)

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Created June 14, 2019

