



# MS-264 ENGRAVED PLASTIC TAGS

## Technical Data

### Description

MS-264 tags are ideal for marking electrical equipment and control panels. Engraved information clearly shows against the background color. Letter size will be adjusted to fit available space or specification requirement. Standard tag construction is 2 ply 1/16" thick.

Although MS-264 is not a thermoset plastic (phenolic) as designated by ASTM-D709 it is a fire-retardant polymer specifically designed as a safer, formaldehyde and phenol free, alternative to phenolic. MS-264 is non-flammable, UL 94 VO rated, electrically non-conductive, and insulative. Tags are also RoHS compliant, halogen free and PVC free.



### Physical and Chemical Characteristics

<b>Standard Material:</b>	2-ply (two laminated layers of engraving plastic)	
<b>Optional Material:</b>	3-ply (three laminated layers of engraving plastic)	
<b>Standard Thickness:</b>	1/16" (1.6 mm)	
<b>Optional Thickness:</b>	1/8" (3.2 mm)	
<b>Service Temperature:</b>	-20°F through 175°F (-29°C through 79°C)	
<b>Outdoor Durability:</b>	Indoor use only	
<b>Finish:</b>	Matte finish with beveled edges	
<b>Mounting:</b>	Adhesive backing and/or holes: 3/16" (4.8 mm) default diameter)	
<b>Standard Colors:</b> (Non-standard colors available upon request)	<input type="checkbox"/> BLACK (WHITE text) <input type="checkbox"/> GREEN (WHITE text) <input type="checkbox"/> RED (WHITE text) <input type="checkbox"/> BLUE (WHITE text)	<input type="checkbox"/> WHITE (BLACK text) <input type="checkbox"/> YELLOW (BLACK text) <input type="checkbox"/> ORANGE (BLACK text)
<b>Text Height:</b>	Sized to fit within tag boundary or comply with specified height	

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Created June 14, 2019

