



MS-900 SELF-ADHESIVE CONDUIT AND CABLE MARKERS

Technical Data

110 VOLTS

120 VOLTS

Description

MS-900 self-adhesive conduit and cable are made of a premium grade .004" thick flexible thermoplastic film coated with a permanent acrylic pressure sensitive adhesive. Use MS-900 adhesive labels to identify a plant's electrical services and equipment.

- Designed for labeling conduit, panel boxes, circuit breakers and connections to equipment
- Black text on orange labels provide a highly visible warning of potential electrical hazards
- Custom legends and other color combinations are available

Physical and Chemical Characteristics

Film:	.004" (.1 mm) thick thermoplastic
Adhesive:	Permanent pressure-sensitive acrylic
Service Temperature:	-50°F through +180°F (-45°C thru 82°C)
Application Temperature:	+50°F (10°C)
Water Resistance:	Excellent
Chemical Resistance:	Resistant to mild acids, alkalis and salts
Expected Outdoor Durability:	Indoor use only. Recommend MS-900TO conduit and cable markers for outdoor use.
Storage Durability:	Two years when stored at +73°F (22°C) and 50% relative humidity
Available Sizes (Custom legends and sizes available):	<input type="checkbox"/> 1/2" x 2-1/2" <input type="checkbox"/> 1" x 8" <input type="checkbox"/> 2" x 9"

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Updated on 8/26/2020

