



MS-900TO SELF-ADHESIVE VINYL ARC FLASH LABELS

Technical Data



Description

These premium labels are custom printed with the information and safety header for your specific application. All labels include a safety header and alert symbol. Other information can include incident energy (cal/cm²), hazard category, PPE required and boundary distances. These labels meet then NFPA, NEC, and OSHA requirements. The printed graphics on these labels are protected against the effects of chemicals and fading caused by ultra-violet rays. Self-adhesive MS-900TO labels are made of pre-printed vinyl with a top laminate of ultra-violet resistant clear protective film.

Available Sizes: 3" x 4" & 4" x 6"

**Custom sizes available.

Physical and Chemical Characteristics

Base Material for MS-900:	.0032" (0.0812 mm) thick PVC
Service Temperature:	-50°F through 180°F (-45°C thru 82°C)
Application Temperature:	+50°F (10°C)
Water Resistance:	Excellent
UV Resistance:	Good
Chemical Resistance:	Resistant to acids; alkalis and salts
Expected Outdoor Durability:	Base Material: 5 years
Storage Durability:	Two years when stored at +73°F (22°C) and 50% relative humidity
Finish:	Gloss surface
Text Height:	Sized to fit within label boundary or comply with specified height
Mounting:	Permanent pressure sensitive acrylic adhesive backing

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Created on 7/23/2020

