



MS-975 COILED POLYESTER PIPE MARKERS

Technical Data



Description

MS-975 coiled polyester pipe markers are designed to identify piping in a wide variety of indoor environments. No preparation of the pipe surface is required for application, so installation time is reduced compared to conventional stick-on marker systems. Legends are sub-surface printed so they are protected by a layer of polyester. Markers are held in place by an adhesive strip that sticks to the coiled marker so there is no adhesive touching the pipe.

MS-975 material is available in a wide variety of coil sizes on pipe diameters up to 60 inches. Please inquire for specific sizing - standard sizes below.

Physical and Chemical Characteristics

Standard Material:	.005" (0.127 mm) mil polyester
Service Temperature:	-40°F to +250°F (-40°C to 121°C)
Water Resistance:	Excellent
Outdoor Durability:	Recommended for indoor use only
Density:	1.37
Tensile Strength:	22,000 PSI
Shrinkage:	3% at 190°C for 5 minutes storage
Stability:	Indefinite when stored at room temperature with moderate humidity

Marker Sizes and Letter Heights

Pipe Diameter	Style Marker	Marker Width	Character Height	Marker Type
1/2" – 1"	A	8"	1/2"	COIL-ON
1-1/8" – 2-1/4"	B	8"	3/4"	COIL-ON
2-3/8" – 3-1/4"	C	12"	1-1/4"	COIL-ON
3-3/8" – 4-1/2"	D	12"	1-1/4"	COIL-ON
4-5/8" – 5-7/8"	E	12"	1-1/4"	COIL-ON
6" – 7-7/8"	F	12"	1-1/4"	COIL-ON
8" – 10"	J*	12"	1-1/4"	COIL-ON
11" – 12"	K*	12"	1-1/4"	COIL-ON

*J and K available in 24" and 32" to meet ASME 13.1 sizing.





MS-975 COILED POLYESTER PIPE MARKERS

Technical Data

Designation of Colors (ASME A13.1-2015 & ANSI Z535-2017)

Designation of Colors — ASME A13.1-2015 & ANSI Z535-2017 Standards		
Classification	Color Scheme	
Defined Applications		
Fire quenching liquids	White text on red	Sample
Toxic and corrosive fluids	Black text on orange	Sample
Flammable fluids	Black text on yellow	Sample
Combustible fluids	White text on brown	Sample
Potable, cooling, boiler feed and other water	White text on green	Sample
Compressed air	White text on blue	Sample
Undefined Applications		
Defined by user	White text on purple	Sample
Defined by user	Black text on white	Sample
Defined by user	White text on gray	Sample
Defined by user	White text on black	Sample

Designation of Colors (ANSI/ASME A13.1-1996)

Designation of Colors — ANSI/ASME A13.1-1996 Standards		
Classification	Color Scheme	
Materials Inherently Hazardous		
Flammable or Explosive, Chemically Active or Toxic, Extreme Temperature or Pressures, Radioactive	Black text on yellow	Sample
Materials Inherently Low Hazard		
Liquid or Liquid Admixture (non-hazardous materials)	White text on green	Sample
Gas or Gaseous Admixture (non-hazardous materials)	White text on blue	Sample
Fire Quenching Materials		
Water, Foam, CO2, Halon, etc.	White text on red	Sample

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Created on 7/1/2015

