



MS-900 SELF-ADHESIVE BANDING TAPE

Technical Data

Description

MS-900 self-adhesive banding tape is constructed using a premium grade .004" thick flexible thermoplastic film coated with a permanent acrylic pressure sensitive adhesive. This tape is used to provide indoor or outdoor system color coding. Recommend adding MS-1000 UV Overlamine for outdoor use.

- Complies with MIL-SPEC 101B
- Standard sizes: 1" (25 mm) and 2" (51 mm) wide by 50 yds (46 m) long.
- Also available in 3" (76 mm), 4" (102 mm), and 6" (152 mm) rolls.



Physical and Chemical Characteristics

Base Material:	Premium-grade Thermoplastic
Material Thickness:	.004" (.1 mm)
Service Temperature:	-50°F to 180°F (-45°C to 82°C)
Application Temperature:	+50°F (10°C)
Chemical Resistance:	Good
Water Resistance:	Excellent
Expected Outdoor Durability:	Indoor Use Only
Storage Durability:	Up to 2 Years
Abrasion Resistance:	Good
Mounting:	Permanent pressure sensitive acrylic adhesive backing
Finish:	n/a
Text Height:	n/a
Typical Sizes:	1" (25 mm) and 2" (51 mm) wide by 50 yds (46 m) long.
Standard Colors:	Designed to meet ANSI & ASME Standards (See chart)
Options:	Custom Sizes Available
Chemical Table:	Acid Resistance: Good Alkalis Resistance: Good Salts Resistance: Good

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Updated on 11/23/2021





MS-900 SELF-ADHESIVE BANDING TAPE

Technical Data

Designation of Colors (ASME A13.1-2015 & ANSI Z535-2017)

Designation of Colors — ASME A13.1-2015 & ANSI Z535-2017 Standards		
Classification	Color Scheme	
Defined Applications		
Fire quenching liquids	White text on red	Sample
Toxic and corrosive fluids	Black text on orange	Sample
Flammable fluids	Black text on yellow	Sample
Combustible fluids	White text on brown	Sample
Potable, cooling, boiler feed and other water	White text on green	Sample
Compressed air	White text on blue	Sample
Undefined Applications		
Defined by user	White text on purple	Sample
Defined by user	Black text on white	Sample
Defined by user	White text on gray	Sample
Defined by user	White text on black	Sample

Designation of Colors (ANSI/ASME A13.1-1996)

Designation of Colors — ANSI/ASME A13.1-1996 Standards		
Classification	Color Scheme	
Materials Inherently Hazardous		
Flammable or Explosive, Chemically Active or Toxic, Extreme Temperature or Pressures, Radioactive	Black text on yellow	Sample
Materials Inherently Low Hazard		
Liquid or Liquid Admixture (non-hazardous materials)	White text on green	Sample
Gas or Gaseous Admixture (non-hazardous materials)	White text on blue	Sample
Fire Quenching Materials		
Water, Foam, CO2, Halon, etc.	White text on red	Sample

