



## MS-215R REFLECTIVE TAGS

## Technical Data



### Description

MS-215R reflective tags are constructed of printed graphics sealed between layers of chemical resistant plastic. The top layer is an outdoor durable thermoplastic that provides excellent resistance to process chemicals, protection from high impact and functions as a UV filter to prevent fading of printing and graphics. The graphics layer can be customized to meet the required reflective intensity specification. The base substrate provides excellent stiffness for rigid tag requirements. The tag construction has been tested with chemicals common to pulp, paper mills and petrochemical facilities with no adverse effect. Wind tunnel tested to 200 mph.

### Physical and Chemical Characteristics

<b>Base Material:</b>	Rigid Thermoplastic	
<b>Material Thickness:</b>	.100" (2.54 mm)	
<b>Service Temperature:</b>	-40°F to 200°F (-40°C to 93°C)	
<b>Application Temperature:</b>	W/ adhesive +50°F (10°C)	
<b>Chemical Resistance:</b>	Excellent	
<b>Water Resistance:</b>	Excellent	
<b>Expected Outdoor Durability:</b>	Excellent (5+ Years), Tested to ASTM D 7869	
<b>Storage Durability:</b>	W/ Adhesive - Up to 2 Years   W/O Adhesive - 5+ Years	
<b>Abrasion Resistance:</b>	Excellent	
<b>Mounting:</b>	Adhesive backing, grommets, holes with washers or foam tape	
<b>Finish:</b>	Matte finish with beveled edges (parallel edges available)	
<b>Text Height:</b>	Sized to fit within tag boundary or comply with specified height	
<b>Typical Sizes:</b>	Customizable (see chart)	
<b>Standard Colors:</b>	Customizable (see chart)	
<b>Options:</b>	Reflective or Photoluminescent	
<b>Chemical Table:</b>	Ethyl Acetate: No visible effect Xylene: No visible effect 40% NaOH: No visible effect Concentrated HCl: No visible effect Gasoline: No visible effect Butyl Cellosolve: No visible effect Toluene: No visible effect	Isopropyl Alcohol: No visible effect Cyclohexanone: No visible effect Acetone: Failure MEK: Failure Methylene Chloride: Failure

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Updated on 11/24/2021

8265 N. Faulkner Road, Milwaukee, WI 53224

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com



## MS-215R REFLECTIVE TAGS

### Technical Data

<b>Standard Colors:</b> <b>(Non-standard colors available upon request)</b>	<input type="checkbox"/> BLACK (WHITE text) <input type="checkbox"/> GREEN (WHITE text) <input type="checkbox"/> RED (WHITE text) <input type="checkbox"/> BLUE (WHITE text)	<input type="checkbox"/> BROWN (WHITE text) <input type="checkbox"/> WHITE (BLACK text) <input type="checkbox"/> YELLOW (BLACK text) <input type="checkbox"/> ORANGE (BLACK text)
<b>Typical Sizes (H x W):</b>	<input type="checkbox"/> 1.5" (38 mm) diameter <input type="checkbox"/> 1.5" x 1.5" (38 x 38 mm) <input type="checkbox"/> 1" x 3" (25 x 76 mm) <input type="checkbox"/> 2" x 4" (51 x 102 mm) <input type="checkbox"/> 4" x 8" (102 x 203 mm) <input type="checkbox"/> 10" x 14" (254 x 356 mm) <input type="checkbox"/> 2" (51 mm) diameter	<input type="checkbox"/> 2" x 2" (51 x 51 mm) <input type="checkbox"/> 2" x 3" (51 x 76 mm) <input type="checkbox"/> 3" x 6" (76 x 152 mm) <input type="checkbox"/> 7" x 12" (178 x 305 mm) <input type="checkbox"/> 12" x 20" (305 x 508 mm) <input type="checkbox"/> Other (specify: H x W)
<b>Text Height:</b>	Sized to fit within tag boundary or comply with specified height	