



MS-215R TAGS

Technical Data



Description

MS-215R Tags are constructed of printed graphics sealed between layers of chemical resistant plastic. The top layer is a outdoor durable thermoplastic that provides excellent resistance to process chemicals, protection from high impact and functions as a UV filter to prevent fading of printing and graphics. The substrate provides excellent stiffness for rigid sign requirements. The construction has been tested with chemicals common to pulp, paper mills and petrochemical facilities with no adverse effect. Wind tunnel tested to 200 mph.

Physical and Chemical Characteristics

Base Material:	Rigid Thermoplastic	
Material Thickness:	.100" (2.54 mm)	
Service Temperature:	-40°F to 200°F (-40°C to 93°C)	
Application Temperature:	W/ adhesive +50°F (10°C)	
Chemical Resistance:	Excellent	
Water Resistance:	Excellent	
Expected Outdoor Durability:	Excellent (5+ Years). Tested to ASTM D 7869	
Storage Durability:	W/ Adhesive - Up to 2 Years W/O Adhesive - 5+ Years	
Abrasion Resistance:	Excellent	
Mounting:	Adhesive backing, grommets, holes with washers or foam tape	
Finish:	Matte finish with beveled edges (parallel edges available)	
Text Height:	Sized to fit within tag boundary or comply with specified height	
Typical Sizes:	Customizable (See Chart)	
Standard Colors:	Customizable (See Chart)	
Options:	Reflective or Photoluminescent	
Chemical Table:	Ethyl Acetate: No visible effect Xylene: No visible effect 40% NaOH: No visible effect Concentrated HCl: No visible effect Gasoline: No visible effect Butyl Cellosolve: No visible effect Toluene: No visible effect	Isopropyl Alcohol: No visible effect Cyclohexanone: No visible effect Acetone: Failure MEK: Failure Methylene Chloride: Failure



MS-215R TAGS AND SIGNS

Technical Data

Standard Colors: (Non-standard colors available upon request)	<input type="checkbox"/> BLACK (WHITE text) <input type="checkbox"/> GREEN (WHITE text) <input type="checkbox"/> RED (WHITE text) <input type="checkbox"/> BLUE (WHITE text)	<input type="checkbox"/> BROWN (WHITE text) <input type="checkbox"/> WHITE (BLACK text) <input type="checkbox"/> YELLOW (BLACK text) <input type="checkbox"/> ORANGE (BLACK text)
Typical Sizes (H x W):	<input type="checkbox"/> 1.5" (38 mm) diameter <input type="checkbox"/> 1.5" x 1.5" (38 x 38 mm) <input type="checkbox"/> 1" x 3" (25 x 76 mm) <input type="checkbox"/> 2" x 4" (51 x 102 mm) <input type="checkbox"/> 4" x 8" (102 x 203 mm) <input type="checkbox"/> 10" x 14" (254 x 356 mm) <input type="checkbox"/> 2" (51 mm) diameter	<input type="checkbox"/> 2" x 2" (51 x 51 mm) <input type="checkbox"/> 2" x 3" (51 x 76 mm) <input type="checkbox"/> 3" x 6" (76 x 152 mm) <input type="checkbox"/> 7" x 12" (178 x 305 mm) <input type="checkbox"/> 12" x 20" (305 x 508 mm) <input type="checkbox"/> Other (specify: H x W)
Text Height:	Sized to fit within tag boundary or comply with specified height	

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Updated on 11/24/2021