




## MS-260R PHOTOLUMINESCENT SIGNS

### Technical Data



#### Description

MS-260R Signs are constructed of printed graphics sealed between layers of chemical resistant plastic. The top layer is an outdoor durable thermoplastic that provides excellent resistance to process chemicals, protection from high impact and functions as a UV filter to prevent fading of printing and graphics. Safety grade photoluminescent is designed to glow 8+ hours. The .100" thick base provides excellent stiffness for rigid sign requirements. The construction has been tested with chemicals common to pulp, paper mills and petrochemical facilities with no adverse effect. Wind tunnel tested to 200 mph. MS-260R Photoluminescent material meets the ISO standard for Low Level/Low Location Lighting.

#### Physical and Chemical Characteristics

<b>Base Material:</b>	.100" (2.54 mm) Acrylic/ABS
<b>Material Thickness:</b>	Single Sided: .118" (3 mm) Double Sided: .136" (3.45 mm), 1 base, 2 each label, 2 each top layer
<b>Service Temperature:</b>	-40°F through 200°F (-40°C thru 93°C)
<b>Application Temperature:</b>	w/ adhesive 50°F (10°C)
<b>Chemical Resistance:</b>	Excellent
<b>Water Resistance:</b>	Excellent
<b>Expected Outdoor Durability:</b>	Excellent (5+ Years)
<b>Storage Durability:</b>	5 years minimum
<b>Abrasion Resistance:</b>	Excellent
<b>Mounting:</b>	Adhesive backing, grommets, holes with washers or foam tape
<b>Finish:</b>	Matte finish with beveled edges (parallel edges available)
<b>Text Height:</b>	Customizable (See Chart Below)
<b>Typical Sizes:</b>	Customizable (See Chart Below)
<b>Standard Colors:</b>	Customizable (See Chart Below)
<b>Options:</b>	n/a
<b>Chemical Table:</b>	Ethyl Acetate: No visible effect; Xylene: No visible effect; 40% NaOH: No visible effect; Concentrated HCl: No visible effect; Gasoline: No visible effect; Butyl Cellosolve: No visible effect; Toluene: No visible effect; Isopropyl Alcohol: No visible effect; Cyclohexanone: No visible effect; Acetone: Failure; MEK: Failure; Methylene Chloride: Failure



## MS-260R PHOTOLUMINESCENT SIGNS

### Technical Data

<b>Luminous Values:</b> <b>Standard Safety Grade (Optional High Performance Safety Grade available)</b>	DIN 67510/ASTM 2072 (Xe lamp 1000Lx/5 min) 10 min                      56 mcd/m <sup>2</sup> (Xe lamp 1000Lx/5 min) 60 min                      7 mcd/m <sup>2</sup>	
<b>Luminous Compliance:</b>	DIN 67510, ASTM 2072, ISO 15370:2010, EU marine Equipment Directive, IMO RES A. 752 (18), PSPA class B	
<b>Standard Colors:</b> <b>(Non-standard colors available upon request)</b>	<input type="checkbox"/> BLACK (WHITE text) <input type="checkbox"/> GREEN (WHITE text) <input type="checkbox"/> RED (WHITE text)	<input type="checkbox"/> BLUE (WHITE text) <input type="checkbox"/> BROWN (WHITE text) <input type="checkbox"/> WHITE (BLACK text)
<b>Typical Sizes (H x W):</b>	<input type="checkbox"/> 1.5" (38 mm) diameter <input type="checkbox"/> 1.5" x 1.5" (38 x 38 mm) <input type="checkbox"/> 1" x 3" (25 x 76 mm) <input type="checkbox"/> 2" x 4" (51 x 102 mm) <input type="checkbox"/> 4" x 8" (102 x 203 mm) <input type="checkbox"/> 10" x 14" (254 x 356 mm) <input type="checkbox"/> 2" (51 mm) diameter	<input type="checkbox"/> 2" x 2" (51 x 51 mm) <input type="checkbox"/> 2" x 3" (51 x 76 mm) <input type="checkbox"/> 3" x 6" (76 x 152 mm) <input type="checkbox"/> 7" x 12" (178 x 305 mm) <input type="checkbox"/> 12" x 20" (305 x 508 mm) <input type="checkbox"/> Other (specify: H x W)
<b>Text Height:</b>	Sized to fit within sign boundary or comply with specified height	

*Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.*

Updated on 11/29/2021