MS-900 SELF-ADHESIVE ARC FLASH LABELS

Technical Data



Description

These premium labels are custom printed with the information and safety header for your specific application. All labels include a safety header and alert symbol. Other information can include incident energy (cal/cm2), hazard category, PPE required and boundary distances. These labels meet the NFPA, NEC, and OSHA requirements. Self-adhesive MS-900 labels are made of pre-printed thermoplastic film with a permanent acrylic pressure sensitive adhesive

Available Sizes: 3" x 4" & 4" x 6" **Custom sizes available.

Physical and Chemical Characteristics

Base Material:	Premium-grade Thermoplastic
Material Thickness:	.004" (.1 mm)
Service Temperature:	-50°F to 180°F (-45°C to 82°C)
Application Temperature:	+50°F (10°C)
Chemical Resistance:	Good
Water Resistance:	Excellent
Expected Outdoor Durability:	Indoor Use Only
Storage Durability:	Up to 2 Years
Abrasion Resistance:	Good
Mounting:	Permanent pressure sensitive acrylic adhesive backing
Finish:	n/a
Text Height:	Sized to fit within label boundary or comply with specified height
Typical Sizes:	3" x 4" & 4" x 6"
Standard Colors:	Orange, Red, Yellow
Options:	Custom Sizes Available
Chemical Table:	n/a

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without quarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Revised on 11/23/2021

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com