WHITE ENAMELED ALUMINUM TAGS W/ UV OVERLAMINATE

Technical Data

PURGE PANEL SUPPLY VALVE

HOT WORK PERMIT
REQUIRED OR
DE-ENERGIZE EQUIPMENT
PRIOR TO CLOSING VALVE

Description

White Enamel Aluminum W/ UV Overlaminate. Use for equipment plates to show model name and characteristics specific to a piece of equipment. Can be used to show maintenance instructions and operating procedures. Durable both indoors or outdoors. Available in 1"x3", 2"x4", 4"x6", 5"x7", 7"x10", 10"x14", and 14"x20" plates. Equipment tags come with standard 3/16" mounting holes or adhesive. Custom sizes available.

Solid Brass or Stainless Steel "S" hooks or jack chain is used to attach tag to provide a tough, sturdy and corrosion resistant fastener.

Physical and Chemical Characteristics

Base Material:	White Enamel Aluminum W/ UV Overlaminate
Material Thickness:	.033" (.84 mm)
Service Temperature:	-40°F to 180°F (-40°C to 83°C)
Application Temperature:	W/ adhesive +50°F (10°C)
Chemical Resistance:	Excellent
Water Resistance:	Excellent
Expected Outdoor Durability:	Excellent (5 + Years)
Storage Durability:	W/ Adhesive - Up to 2 Years W/O Adhesive - 5+ Years
Abrasion Resistance:	Very Good
Mounting:	Adhesive backing and/or holes
Finish:	Gloss finish
Text Height:	Sized to fit within tag boundary or comply with specified height
Typical Sizes:	Customizable
Standard Colors:	n/a
Options:	n/a
Chemical Table:	n/a

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without quarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Revised on 3/2/2022