WHITE ENAMELED ALUMINUM SIGNS & TAGS

Technical Data

PURGE PANEL SUPPLY VALVE

HOT WORK PERMIT
REQUIRED OR
DE-ENERGIZE EQUIPMENT
PRIOR TO CLOSING VALVE

Description

White Enamel Aluminum. Use for equipment plates to show model name and characteristics specific to a piece of equipment. Can be used to show maintenance instructions and operating procedures.

For indoor use only. Available with UV Overlaminate or Rugged-Kote for outdoor use.

Available in 1"x3", 2"x4", 4"x6", 5"x7", 7"x10", 10"x14", and 14"x20" plates. Equipment tags come with standard 3/16" mounting holes or adhesive. Custom sizes available.

Solid Brass or Stainless Steel "S" hooks or jack chain is used to attach tag to provide a tough, sturdy and corrosion resistant fastener.

Physical and Chemical Characteristics

| Base Material: | White Enamel Aluminum |
|-------------------------------------|--|
| Material Thickness: | .032" (.81 mm) |
| Service Temperature: | -40°F to 180°F (-40°C to 83°C) |
| Application Temperature: | W/ adhesive +50°F (10°C) |
| Chemical Resistance: | Good |
| Water Resistance: | Excellent |
| Expected Outdoor Durability: | Indoor Use Only |
| Storage Durability: | W/ Adhesive - Up to 2 Years W/O Adhesive - 5+ Years |
| Abrasion Resistance: | Good |
| Mounting: | Adhesive backing and/or holes |
| Finish: | Gloss finish |
| Text Height: | Sized to fit within tag boundary or comply with specified height |
| Typical Sizes: | Customizable |
| Standard Colors: | n/a |
| Options: | Add UV Overlaminate or Rugged-Kote for outdoor use |
| Chemical Table: | n/a |

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without quarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

Revised on 10/16/2023