



## MS-900 SELF-ADHESIVE ECONOMY PIPE MARKERS

Technical Data



### Description

MS-900 Self-Adhesive Economy Markers are a cost effective, efficient method of marking the contents and direction of the flow on process piping in safety conscious environments. Economy markers are constructed of a 4 mil pressure sensitive thermoplastic film. Complies with ASME A13.1 color scheme requirement. However, Economy markers do not comply with the length of the color field per ASME. Supplied in rolls of 50 perforated markers and arrows.

### Physical and Chemical Characteristics

<b>Base Material:</b>	Premium-grade Thermoplastic
<b>Material Thickness:</b>	.004" (.1 mm)
<b>Service Temperature:</b>	-50°F to 180°F (-45°C to 82°C)
<b>Application Temperature:</b>	+50°F (10°C)
<b>Chemical Resistance:</b>	Good
<b>Water Resistance:</b>	Excellent
<b>Expected Outdoor Durability:</b>	Indoor Use Only
<b>Storage Durability:</b>	Up to 2 Years
<b>Abrasion Resistance:</b>	Good
<b>Mounting:</b>	Permanent pressure sensitive acrylic adhesive backing
<b>Finish:</b>	n/a
<b>Text Height:</b>	1-1/4" (32 mm) letters
<b>Typical Sizes:</b>	2" x 9" (51 mm x 229 mm)
<b>Standard Colors:</b>	Designed to meet ANSI & ASME Standards (See chart)
<b>Options:</b>	Custom Sizes Available
<b>Chemical Table:</b>	Acid Resistance: Good Alkalis Resistance: Good Salts Resistance: Good

*Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.*

Updated on 1/15/2024

8265 N. Faulkner Road, Milwaukee, WI 53224

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com



# MS-900 SELF-ADHESIVE ECONOMY PIPE MARKERS

Technical Data

## Designation of Colors (ASME A13.1-2023 & ANSI Z535-2017)

Designation of Colors — ASME A13.1-2023 & ANSI Z535-2017 Standards		
Classification	Color Scheme	
<b>Defined Applications</b>		
Firefighting	White text on red	Sample
Toxic or corrosive	Black text on orange	Sample
Flammable, combustible, or oxidizing	Black text on yellow	Sample
Steam; or steam condensate, boiler feedwater, or other hot water	Black text on gray	Sample
Potable, cooling, or other cold or tepid water	White text on green	Sample
Compressed air	White text on blue	Sample
<b>Undefined Applications</b>		
Defined by user	White text on purple	Sample
Defined by user	Black text on white	Sample
Defined by user	White text on brown	Sample
Defined by user	White text on black	Sample

## Designation of Colors (ANSI/ASME A13.1-1996)

Designation of Colors — ANSI/ASME A13.1-1996 Standards		
Classification	Color Scheme	
<b>Materials Inherently Hazardous</b>		
Flammable or Explosive, Chemically Active or Toxic, Extreme Temperature or Pressures, Radioactive	Black text on yellow	Sample
<b>Materials Inherently Low Hazard</b>		
Liquid or Liquid Admixture (non-hazardous materials)	White text on green	Sample
Gas or Gaseous Admixture (non-hazardous materials)	White text on blue	Sample
<b>Fire Quenching Materials</b>		
Water, Foam, CO2, Halon, etc.	White text on red	Sample