

# MS-900 SELF-ADHESIVE PIPE MARKERS W/ UV OVERLAMINATE

**Technical Data** 

#### **Description**

## CHILLED WATER SUPPLY

## NATURAL GAS

MS-900 UV Self-Adhesive Pipe Markers are specially designed for outdoor use. They are manufactured from premium grade thermoplastic with a permanent pressure sensitive adhesive. The film and graphics are laminated with UV Overlaminate providing not only additional chemical resistance but also excellent UV and fade resistance for extended outdoor durability. They are used to provide line service designations, system color-coding or various labeling needs. MS-900 UV markers conform to the ASME A 13.1 "Scheme for the Identification of Piping Systems" with regard to label colors, overall size and text height. Flow directional arrow tape or individual arrow markers are used with pipe markers to indicate direction of flow. MS-900 UV markers are available in a variety of standard and custom colors including clear.

#### **Physical and Chemical Characteristics**

Base Material:	Premium-grade Thermoplastic w/ UV Overlaminate		
Material Thickness:	.005" (.127 mm)		
Service Temperature:	-50°F to 180°F (-45°C to 82°C)		
Application Temperature:	+50°F (10°C)		
Chemical Resistance:	Excellent		
Water Resistance:	Excellent		
<b>Expected Outdoor Durability:</b>	Very Good (Up to 5 Years) Tested to ASTM D 7869		
Storage Durability:	Up to 2 Years		
Abrasion Resistance:	Very Good		
Mounting:	Permanent pressure sensitive acrylic adhesive backing		
Finish:	Gloss Surface		
Text Height:	Designed to meet ANSI & ASME Standards (See chart)		
Typical Sizes:	Designed to meet ANSI & ASME Standards (See chart)		
Standard Colors:	Designed to meet ANSI & ASME Standards (See chart)		
Options:	Custom Sizes Available		
Chemical Table:	Acid Resistance: Good Alkalis Resistance: Good Salts Resistance: Good		

### Label Sizes and Text Heights

Marker Size	Pipe Diameter (Including insulation)	Marker Style	Color Field	Text Height
1" x 8"	3/4" – 2-1/4"	А	8" long	3/4"
2-1/4" x 13"	2-1/2" – 7-7/8"	В	13" long	1-3/4"
4" x 24"	8" - 10"	С	24" long	2-1/2"
4" x 32"	Over 10"	D	32" long	3-1/2"

\*Individual arrow markers are the same width and one-half the length of the pipe markers.

#### 8265 N. Faulkner Road, Milwaukee, WI 53224

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com



## MS-900 SELF-ADHESIVE PIPE MARKERS W/ UV OVERLAMINATE Tech

**Technical Data** 

### Designation of Colors (ASME A13.1-2023 & ANSI Z535-2017)

Designation of Colors — ASME A13.1-2023 & ANSI Z535-2017 Standards					
Classification	Color Scheme				
Defined Applications					
Firefighting	White text on red	Sample			
Toxic or corrosive	Black text on orange	Sample			
Flammable, combustible, or oxidizing	Black text on yellow	Sample			
Steam; or steam condensate, boiler feedwater, or other hot water	Black text on gray	Sample			
Potable, cooling, or other cold or tepid water	White text on green	Sample			
Compressed air	White text on blue	Sample			
Undefined Applications					
Defined by user	White text on purple	Sample			
Defined by user	Black text on white	Sample			
Defined by user	White text on brown	Sample			
Defined by user	White text on black	Sample			

### Designation of Colors (ANSI/ASME A13.1-1996)

Designation of Colors — ANSI/ASME A13.1-1996 Standards					
Classification	Color Scheme				
Materials Inherently Hazardous					
Flammable or Explosive, Chemically Active or Toxic, Extreme Temperature or Pressures, Radioactive	Black text on yellow	Sample			
Materials Inherently Low Hazard					
Liquid or Liquid Admixture (non-hazardous materials)	White text on green	Sample			
Gas or Gaseous Admixture (non-hazardous materials)	White text on blue	Sample			
Fire Quenching Materials					
Water, Foam, CO2, Halon, etc.	White text on red	Sample			

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.