



Plastic Reusable Stencils

Technical Data



STEAM

Description

Pre-cut stencils can be made in several different sizes to meet the requirements of the piping or equipment to be marked. Standard stencils are available with 1/2", 3/4", 1", 2"-1/2" and 3-1/2" letter heights and/or to comply with ASME A13.1 recommendations.

Directional arrows are also available either separately or with legend to correctly indicate direction of flow in the piping.

Ductwork and equipment legends are also available to accurately identify ducts and equipment within a facility.

Physical and Chemical Characteristics

Standard Material:	Reusable Plastic
Standard Thickness:	0.010" (0.406 mm)
Standard Letter Height:	<div><input type="checkbox"/> 0.5" (12.7 mm) <input type="checkbox"/> 0.75" (19 mm) <input type="checkbox"/> 1" (25.4 mm) <input type="checkbox"/> 2" (50.8 mm) <input type="checkbox"/> 2.5" (63.5 mm) <input type="checkbox"/> 3.5" (88.9 mm) <input type="checkbox"/> Other</div>

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

8265 N. Faulkner Road, Milwaukee, WI 53224

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com

Revised 8/26/2025