



MS-900 Self-Adhesive Pipe Markers

Technical Data

CHILLED WATER SUPPLY

NATURAL GAS

Description

MS-900 Self-Adhesive Pipe markers are manufactured from premium grade thermoplastic with a permanent pressure-sensitive acrylic adhesive. They are used to provide line service designations, system color-coding or various labeling needs. MS-900 Markers conform to the ASME A 13.1 "Scheme for the Identification of Piping Systems" with regard to label colors, overall size, and text height. Flow directional arrow tape or individual arrow markers are used with pipe markers to indicate direction of flow. MS-900 Markers are available in a variety of standard and custom colors. These Markers are approved for use in applications using CPVC piping. Also available with an optional scored arrow.

Physical and Chemical Characteristics

Base Material:	Premium-grade Thermoplastic
Material Thickness:	0.004" (0.1 mm)
Service Temperature:	-50°F to 180°F (-45°C to 82°C)
Application Temperature:	+50°F (10°C)
Chemical Resistance:	Good
Water Resistance:	Excellent
Expected Outdoor Durability:	Indoor Use Only
Storage Durability:	Up to 2 Years
Abrasion Resistance:	Good
Mounting:	Permanent pressure sensitive acrylic adhesive backing
Finish:	Gloss Surface
Text Height:	Designed to meet ANSI & ASME Standards (See chart)
Typical Sizes:	Designed to meet ANSI & ASME Standards (See chart)
Standard Colors:	Designed to meet ANSI & ASME Standards (See chart)
Options:	Custom Sizes Available
Chemical Table:	Acid Resistance: Good Alkalis Resistance: Good Salts Resistance: Good

Label Sizes & Letter Heights

Pipe Diameter (Including insulation)	Marker Size	Marker Style	Color Field	Letter Height
3/4" – 2-3/8"	1" x 8"	A	8" long	3/4"
2-1/2" – 6-3/4"	2-1/4" x 13"	B	13" long	1-3/4"
6-3/4" – 10"	4" x 24"	C	24" long	2-1/2"
Over 10"	4" x 32"	D	32" long	3-1/2"

*Individual arrow markers are the same width and one-half the length of the pipe markers

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

8265 N. Faulkner Road, Milwaukee, WI 53224

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com



MS-900 Self-Adhesive Pipe Markers

Technical Data

Designation of Colors (ASME A13.1-2023 & ANSI Z535-2017)

Designation of Colors — ASME A13.1-2023 & ANSI Z535-2017 Standards		
Classification	Color Scheme	
Defined Applications		
Firefighting	White text on red	Sample
Toxic or corrosive	Black text on orange	Sample
Flammable, combustible, or oxidizing	Black text on yellow	Sample
Steam; or steam condensate, boiler feedwater, or other hot water	Black text on gray	Sample
Potable, cooling, or other cold or tepid water	White text on green	Sample
Compressed air	White text on blue	Sample
Undefined Applications		
Defined by user	White text on purple	Sample
Defined by user	Black text on white	Sample
Defined by user	White text on brown	Sample
Defined by user	White text on black	Sample

Designation of Colors (ASME A13.1-2015 & ANSI Z535-2017)

Designation of Colors — ASME A13.1-2015 & ANSI Z535-2017 Standards		
Classification	Color Scheme	
Defined Applications		
Fire quenching liquids	White text on red	Sample
Toxic and corrosive fluids	Black text on orange	Sample
Flammable fluids	Black text on yellow	Sample
Combustible fluids	White text on brown	Sample
Potable, cooling, boiler feed and other water	White text on green	Sample
Compressed air	White text on blue	Sample
Undefined Applications		
Defined by user	White text on purple	Sample
Defined by user	Black text on white	Sample
Defined by user	White text on gray	Sample
Defined by user	White text on black	Sample

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

8265 N. Faulkner Road, Milwaukee, WI 53224

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com

Revised 3/27/2026